

5 May 2026

Impacts of Heavy Vehicle Reform
Productivity Commission
Locked Bag 2 Collins St
East Melbourne VIC 8003

Submitted via: [Impacts of heavy vehicle reform - Commissioned study | Productivity Commission](#)

Submission on Interim Report – Impacts of Heavy Vehicle Reform

Dear Commissioners

CCAA welcomes the opportunity to comment on the Productivity Commission's Interim Report into the Impacts of Heavy Vehicle Reform.

CCAA is the voice of the heavy construction materials industry representing cement manufacturers, concrete suppliers and extractive operators throughout Australia. Our members range from large global companies to SMEs and family operated businesses engaged in quarrying, cement manufacture and concrete production. These operations underpin construction and infrastructure delivery across all jurisdictions and rely on efficient, predictable and productive heavy vehicle movements.

A report for CCAA by Oxford Economics confirms that the [industry contributes](#) \$20.7 billion to GDP and supports more than 112,000 jobs nationally¹.

CCAA considers that the Interim Report is directionally sound and reflects many of the issues raised in our earlier submission (see Attachment A - *Submission to Productivity Commission Request for Advice Heavy Vehicle Reform December 2025*).

CCAA supports the Commission's focus on access reform as the primary productivity lever, and its recognition of the systemic barriers associated with PBS access, local road constraints and fragmented decision-making.

Critically, achieving these productivity gains is contingent on the capability and condition of the underlying road network. Without sustained investment in road maintenance, renewals and asset management capability, increased vehicle mass, dimension or access reforms will not translate into real productivity gains and may instead exacerbate network deterioration, safety risks and community impacts.

We reiterate our position that while vehicle capability has improved significantly over time, the broader system settings that govern access, funding, planning and infrastructure have not kept pace. As a result, productivity outcomes have plateaued, and further gains will depend on reform to these interconnected systems rather than incremental changes to vehicle standards alone.

CCAA therefore emphasises that implementation must address underlying system constraints - particularly network capability, funding alignment and asset management - if reforms are to deliver sustainable productivity outcomes.

¹ [Oxford Economics – Economic Contribution of the CCA Industry in Australia – March 2026](#)

1. Areas of strong support

CCAA strongly supports the overall direction of the Interim Report, and particularly the Commission's emphasis on improving access as the central mechanism for unlocking productivity.

The focus on expanding as-of-right access and reducing reliance on permit-based systems is appropriate and necessary. Current arrangements impose unnecessary administrative burden, create uncertainty and delay investment in higher productivity vehicles. Greater use of network-based access frameworks, particularly for PBS vehicles, will improve efficiency and provide more predictable outcomes for operators.

CCAA also strongly supports the development of the National Automated Access System (NAAS). A nationally consistent, data-driven approach to access decision-making is critical to addressing fragmentation across jurisdictions and improving timeliness and transparency. The shift toward network-based access rather than prescriptive route approvals is a key reform.

We further support the Commission's recognition of the barriers facing zero-emission heavy vehicles, including payload penalties and infrastructure constraints, as well as its findings in relation to curfew reform and the need to reconsider operating restrictions in light of modern vehicle performance.

2. Response to information requests – Mass, Dimension and Access Reforms

CCAA has prepared a detailed submission on the proposed Heavy Vehicle (Mass, Dimension and Loading) National Regulation changes (see Attachment B *Submission to NTC - Heavy Vehicle National Regulation Amendment January 2026*). The following summarises our key positions.

2.1 Alignment of General Mass Limits with Concessional Mass Limits

CCAA supports aligning General Mass Limits with Concessional Mass Limits as a means of modernising baseline access settings and reflecting the capability of the current fleet. This reform will simplify compliance, reduce reliance on accreditation for routine operations and deliver incremental productivity improvements.

However, these benefits are contingent on maintaining appropriate compliance tolerances. The proposed removal of the one-tonne tri-axle mass transfer allowance (1TMTA) is of significant concern. For construction materials freight, axle loads are inherently variable due to the dynamic nature of the product. The 1TMTA functions as a necessary compliance buffer rather than a productivity concession.

Its removal would introduce a hard compliance cap that will result in systematic under-loading by operators seeking to manage compliance risk. This would materially erode the intended productivity benefits of the reform and, in some cases, result in worse outcomes than the current framework. CCAA therefore strongly recommends that the 1TMTA be retained.

2.2 Increase in prescriptive length to 20 metres

CCAA supports the increase in general access length from 19 metres to 20 metres. This change has the potential to mainstream configurations that currently require PBS approval and improve operational flexibility.

However, for mass-constrained freight tasks, increased length does not in itself deliver productivity benefits. Without corresponding increases in allowable mass, operators remain constrained by payload limits and cannot utilise the additional length effectively.

To deliver meaningful outcomes, length reforms must be explicitly linked to appropriate mass settings. Absent this linkage, the reform risks adding complexity without delivering practical benefit and will not reduce reliance on permits or notices.

2.3 Implications for high productivity vehicles

The proposed reforms have the potential to support increased uptake of higher productivity vehicles. However, their effectiveness will depend on broader system conditions.

First, access outcomes will continue to be constrained by first and last mile limitations, particularly on local government roads. Even where vehicles meet updated mass and dimension limits, access to key origins and destinations will remain restricted without targeted infrastructure upgrades and improved assessment capability (more below).

Finally, consistency across jurisdictions remains critical. Divergent approaches to access, mass limits and network definitions will continue to undermine the effectiveness of national reforms.

2.4 Implications for zero-emission heavy vehicles

The proposed reforms do not, on their own, resolve the barriers facing zero-emission heavy vehicles. Battery-electric trucks incur significant tare weight penalties, which translate directly into reduced payload and increased cost per tonne.

Current concession frameworks are insufficient to offset this impact. As a result, zero-emission vehicles for these reasons, as well as their high cost, remain commercially challenging for construction materials applications.

A more comprehensive approach is required, including larger mass concessions, alignment with PBS frameworks, and reform of planning and infrastructure settings to support charging deployment at industrial sites.

3. Additional observations on implementation and system reform

The effectiveness of the proposed reforms will depend fundamentally on the capability, condition and management of the underlying road network. While the Interim Report appropriately focuses on improving access and vehicle productivity, these outcomes will only be realised where the network is engineered, maintained and funded to support them.

3.1 Asset management and network capability

A step change in strategic asset management capability across all levels of government is required to support heavy vehicle reform. This includes improved data on pavement and bridge condition, more consistent engineering assessment methodologies, and forward-looking maintenance and renewal planning.

Evidence suggests that current capability is uneven and, in many cases, inadequate. Analysis by the Grattan Institute² has found that a significant proportion of local governments do not have a complete understanding of the roads and bridges they manage, with around one quarter of councils lacking accurate asset visibility.

Without this capability, reforms that increase vehicle mass, dimension or access risk accelerating network deterioration, reducing safety and undermining service reliability.

² [Grattan Institute - Potholes and pitfalls: How to fix local roads – November 2023](#)

In practical terms, if the network cannot support higher productivity vehicles, the benefits of reform will not be realised and may instead result in a redistribution of cost and risk across the system.

3.2 First and last mile access constraints

First and last mile access remains the binding constraint on productivity for construction materials transport. Even where vehicles comply with updated mass and dimension settings, access to quarries, plants and construction sites is frequently limited by local road conditions and bridge capacity.

Targeted investment in local networks, informed by improved asset data and engineering assessment, is essential to unlock the benefits of broader access reform. Without this, system-wide productivity gains will remain constrained.

3.3 Funding alignment and investment outcomes

There remains a fundamental misalignment between revenue collection and expenditure on the road network. There is insufficient assurance that funds derived from heavy vehicle charging are directed toward road maintenance, renewals and targeted upgrades of the existing network.

The Grattan Institute has identified a persistent structural funding gap in local road maintenance, estimating that councils are under-investing by at least \$1 billion per year and that funding is often poorly targeted or constrained by inefficient grant conditions³.

Local governments, which manage most of the road network, often bear the cost and risk of enabling heavy vehicle access but lack both the resources and incentives to do so.

Strengthening the linkage between road user charging, funding allocation and network outcomes is essential. Increased revenue from industry must translate into demonstrable improvements in road condition, resilience and access capability if reform is to be sustainable and maintain industry and community confidence.

3.4 Local government capability and consistency

Variability in local government capability continues to affect access outcomes. Differences in asset data quality, engineering expertise and assessment processes result in inconsistent and often conservative decision-making.

This issue is particularly acute in rural and regional areas, where a productive freight route may depend on consent from one or more local road managers with limited exposure to high-productivity combinations. In some cases, access can be delayed even where a state road agency has assessed the relevant road and identified no material impediment. This demonstrates the need for nationally consistent assessment tools, clearer escalation pathways, and capability support for local road managers so that access decisions are timely, evidence-based and proportionate to actual risk.

The Grattan Institute has also highlighted that many councils lack the data, systems and technical capacity required to effectively manage their road networks, reinforcing the need for national approaches to asset data standards, service benchmarks and capability uplift.

Targeted and sustained investment in local government capability - including asset data, digital tools and engineering resources - is required to support more consistent, timely and transparent access decisions. This is also critical to the successful implementation of network-based access frameworks.

³ [Grattan Institute - Potholes and pitfalls: How to fix local roads – November 2023](#)

3.5 Implementation of the National Automated Access System (NAAS)

CCAA strongly supports the development of NAAS as a key enabler of reform. However, its effectiveness will depend on the quality and consistency of underlying data and the capability of road managers to maintain it.

Data gaps, inconsistent methodologies and capability constraints across jurisdictions will need to be addressed to ensure that NAAS delivers reliable, network-based access outcomes. This will require sustained coordination and investment across all levels of government.

NAAS must also be sufficiently broad in scope to cover the full range of high-productivity combinations used in construction-materials supply chains. If NAAS is limited to a narrow set of vehicle types, operators will continue to be forced into separate, manual assessment pathways for combinations that deliver the very productivity, safety and emissions benefits the reform is intended to unlock. This creates investment uncertainty and delays fleet deployment, as vehicles cannot be ordered or deployed while access assessments remain unresolved.

NAAS should therefore be progressively expanded to include additional high-productivity configurations, including multi-combination cement tanker configurations, quad cement tanker combinations and other PBS or equivalent vehicles used in cement, concrete and aggregates supply.

3.6 Planning and protection of freight networks

Planning and land-use conflicts continue to constrain freight operations and access outcomes. Encroachment of sensitive land uses on key freight routes can lead to increased restrictions, including curfews and access limitations.

Stronger national alignment is required to protect strategic freight corridors and ensure that access reforms are not undermined by local planning decisions. This includes better integration of freight considerations into land-use planning frameworks and infrastructure strategies.

4. Conclusion

CCAA supports the intent of the Commission's proposed reforms and the overall direction of the Interim Report.

However, the extent to which these reforms deliver practical productivity outcomes will depend on the capability, condition and management of the road network. Without a commensurate uplift in asset management capability, maintenance investment and network performance, increased vehicle mass, dimension or access will not translate into sustained productivity gains.

Stronger alignment is required between road user charging, funding allocation and investment outcomes to ensure that revenue derived from industry is directed toward road maintenance, renewals and targeted network upgrades.

Enabling safe, high-productivity combinations onto suitable networks would deliver benefits beyond operators. By increasing payload efficiency, reducing duplicated trips and improving journey reliability, these reforms can reduce transport costs that flow through to construction businesses, infrastructure delivery and ultimately end consumers.

Importantly, reforms to increase vehicle productivity should be sequenced with, or contingent on, demonstrated improvements in network capability and asset management outcomes.

Addressing these system constraints - alongside access reform, NAAS implementation and planning protections - will be critical to ensuring that heavy vehicle reform delivers safe, efficient and sustainable outcomes over the long term.

CCAA looks forward to continuing to engage with the Commission as the final report is developed

Should officials wish to discuss this matter, please contact CCAA's Industry Policy Director, Mr David Rynne via david.rynn@ccaa.com.au and

Yours sincerely

MICHAEL KILGARIFF
Chief Executive Officer

Attachments

- A. 18 December 2025 - Submission to Productivity Commission Request for Advice Heavy Vehicle Reform
- B. 19 January 2026 - Submission to NTC - Heavy Vehicle National Regulation Amendment

**ATTACHMENT A – CCAA sub to Productivity Commission Request for Advice Heavy
Vehicle Reform**

18 December 2025

Impacts of Heavy Vehicle Reform
Productivity Commission
Locked Bag 2 Collins St
East Melbourne VIC 8003

Submitted via: [Impacts of heavy vehicle reform - Commissioned study | Productivity Commission](#)

Productivity Commission Request for Advice: Heavy Vehicle Reform

Dear Commissioners

Cement Concrete & Aggregates Australia (CCAA) welcomes the opportunity to provide this submission to the Productivity Commission's study into heavy-vehicle reform.

The construction-materials sector performs one of Australia's largest road freight tasks. Recent analysis of CSIRO TRANSIT data shows that cement, concrete and aggregates (CCA) freight has a unique operational profile that differentiates it sharply from the broader road freight sector:

- CCA fleets carry 26% more tonnes per trailer than the national freight average.
- CCA trip distances are 19% shorter, and trip durations 16% shorter, than the Australian freight average.
- CCA's cost performance is extremely efficient, with 68% lower cost per payload tonne and 41% lower cost per tonne-kilometre than the national average.
- The sector accounts for 39% of all annual tonnes moved on Australian roads and 21% of the national tonne-kilometre road freight task.
- CCA freight represents 22% of total national road freight transport costs, reflecting the essential nature of quarry, cement and concrete movements to every construction and infrastructure market.

These metrics demonstrate that CCA freight is high-mass, short-haul, high-frequency and extremely cost-efficient, meaning productivity gains (or losses) in this sector ripple directly into housing, infrastructure and major project delivery across the nation.

This freight underpins the delivery of Australia's housing, transport, energy, water and public infrastructure in every state and territory. Unlike long-haul freight, the CCA task is short-haul, high-frequency and overwhelmingly dependent on local-government roads, which makes the sector highly exposed to planning constraints, inconsistent access rules and local network limitations.

Despite strong fleet modernisation and high uptake of Performance Based Standards (PBS) heavy vehicles (HV's) - including the growing use of PBS-approved Truck & Dog and A-doubles for CCA freight movements - productivity has stalled.

Whilst vehicle capability has advanced; the supporting access, planning and infrastructure systems have not. The result is a structural ceiling on productivity, emissions reduction and supply reliability and diminishing incentives to continue to invest in PBS HV's.

To support improved HV productivity and decarbonisation, we recommend the Commission assist with policy development and critically examine the costs and benefits of the following reforms:

1. A nationally harmonised construction-materials access framework that provides enhanced Concession Mass Limit (CML) and Higher Mass Limit (HML) access on pre-approved gazetted networks for PBS vehicles that meet certain vehicle configuration standards (like the NSW SPECTS and WA AMMS regimes).
2. Different HV road cost recovery and cost allocation approaches such as:
 - a Forward-Looking Cost Base (FLCB) (to ensure total heavy vehicle road user charges reflect the efficient future cost of building, operating and maintaining the road network), and
 - Mass-Distance-Location (MDL) charging (to ensure costs are allocated fairly to HV road users based on the impact they impose on different parts of the network).

These are potential pathways to more sustainable funding streams to enable improved first- and last-mile Local Government access, and essential State Government mapping, evaluation and upgrades of the PBS CML and HML network.

3. Targeted Commonwealth capability programs for Local Governments, including digital tools, asset data, bridge and pavement assessment systems, to support safe, timely and evidence-based HV road access decisions.
4. A targeted, Commonwealth incentive program that links State, Territory & Local Government road funding to agreed KPI's to drive road network and HV productivity performance and accountability. KPI's could include:
 - Kilometres of expanded PBS CML and HML network
 - Journey-time reliability
 - The proportion of the freight network that is mass-constrained
 - The number of structural bottlenecks restricting access.
5. Strengthened HV mass compliance and enforcement activity to ensure accredited, PBS fleets are not disadvantaged and are rewarded for investing in safer and more productive HV's.
6. A stronger national approach to protecting key freight and construction-materials transport corridors - including the use of Commonwealth funding conditions, national planning frameworks, Infrastructure Australia assessment requirements, and coordinated state-federal governance to prevent incompatible land-use encroachment and ensure long-term access for high-productivity HV's.
7. A nationally consistent HV curfew policy that incentivises the adoption of Electric Vehicle (EV) HV's whilst promoting greater operating hour flexibility for non-EV PBS HV's to improve safety, reduce peak-hour congestion exposure and support the reliable delivery of construction materials.

8. A targeted, Commonwealth program that supports HV charging infrastructure planning and costs.

In relation to the National Automated Access System (NAAS), CCAA believes that this represents the most significant modernisation opportunity for HV access since the introduction of PBS. To realise its full productivity potential, the Commonwealth should:

- Fund its national deployment
- Mandate its adoption across all jurisdictions
- Ensure Councils have the tools, capability and data needed to use it effectively, and
- Support the integration of bridge, pavement and telematics datasets into the platform.

NAAS would replace today's manual and inconsistent decision-making with a modern, data-driven, transparent system. This is essential to reduce delays, improve consistency and support evidence-based access outcomes.

Our full supporting submission is provided at **Attachment 1**. A summary of the CSIRO TRANSIT CCA industry road transport profile is at **Attachment 2**.

Should officials wish to discuss this matter, please contact CCAA's Industry Policy Director, Mr David Rynne via david.rynn@ccaa.com.au and

Yours sincerely

MICHAEL KILGARIFF
Chief Executive Officer

About CCAA

CCAA is the voice of the \$15 billion heavy construction materials industry representing cement manufacturers, concrete suppliers, and extractive operators throughout Australia.

Our members range from large global companies to SMEs and family operated businesses and are engaged in the quarrying of sand, stone and gravel, the manufacture of cement and the supply of pre-mixed concrete.

These businesses service local, regional, and national construction and infrastructure markets to meet Australia's building and construction needs through the provision of roads, railways, bridges, ports, airports, hospitals, schools, and footpaths.

Attachment 1: Full CCAA submission

1.0 INTRODUCTION

Australia's construction-materials sector performs one of the nation's largest and most intensive freight tasks. Unlike long-haul freight, this task is short-haul, high-frequency and overwhelmingly dependent on Local Government roads, making the sector acutely exposed to access constraints, inconsistent regulatory settings and planning-system limitations.

Despite strong uptake of PBS vehicles and significant private investment in safer, more efficient fleets, productivity growth has stalled because the systems that govern access, funding, planning and infrastructure have not kept pace. Barriers such as inconsistent first- and last-mile access, slow and fragmented permit processes, outdated PBS network mapping, planning-imposed curfews, limited charging infrastructure for EV trucks, and the absence of coordinated national frameworks now represent the most significant constraints on productivity and decarbonisation for the sector.

This submission outlines the key reforms the Commission should examine to unlock the next wave of productivity and emissions reductions - reforms centred on modernising heavy-vehicle access, aligning funding and pricing with actual network use, strengthening Local Government capability, improving compliance and enforcement, protecting strategic freight corridors and supporting the transition to low- and zero-emission heavy vehicles.

2.0 INCREASING HEAVY VEHICLE ROAD ACCESS TO REDUCE EMISSIONS AND INCREASE PRODUCTIVITY

2.1 Productivity gains achieved through PBS

PBS has delivered some of the most significant improvements in productivity and safety in the history of Australia's construction-materials freight task. The CCA industry was an early adopter of PBS because its short-haul, high-frequency operations magnify the benefits of safer, more efficient vehicles.

PBS vehicles - especially Level 2 3-axle truck and 4-axle dog combinations - offer substantially improved stability, manoeuvrability and load distribution compared with older prescriptive designs. For example:

- Truck and dog PBS combinations operating at CML (57.5t), provide around 15% higher GCM than GML (50.5t), and
- Truck and dog PBS combinations operating at HML (60t), provide around 4% higher GCM than CML (57.5t), resulting in fewer total truck movements, reduced congestion, lower emissions and better utilisation of drivers, plant and fleet assets.

PBS has also enhanced safety outcomes. Vehicles must satisfy strict engineering performance standards, including rollover resistance, swept-path, braking and dynamic stability. When combined with modern technologies such as Electronic Stability Control (ESC), Roll Stability Control (RSC) and advanced suspension systems, PBS combinations demonstrate significantly lower safety risks.

PBS also accelerated the industry-wide adoption of telematics, on-board mass (OBM) systems and NHVAS Mass Management, strengthening compliance and operational transparency. PBS has therefore modernised the industry fleet and delivered clear national productivity benefits.

However, further productivity gains cannot come from vehicle improvements alone. Vehicle technology has advanced faster than the access, funding and regulatory systems that support it. The next gains must come from modernising access rules, reforming heavy-vehicle funding, improving first-/last-mile networks and adopting nationally consistent decision-making.

2.2. Why HV productivity has stalled in the CCA industry

Productivity growth in the construction-materials transport sector has slowed not because of limitations in vehicle capability or operator compliance, but because of structural, regulatory and administrative barriers that constrain the operation of high-performing HV's. Although PBS delivered a dramatic uplift, these gains are increasingly eroded because the access framework has not evolved in parallel.

2.2.1 *Inconsistent, duplicated and very slow permit access decisions between Councils and States & Territories*

A major structural barrier to construction-freight productivity is the fragmented and manual way in which access decisions are made for local and state road managers.

To operate on a route that includes both state and local roads, a heavy-vehicle operator must apply to the NHVR, which then seeks consent from every road manager responsible for each section of the route. The permit can only be issued if **all** road managers - state authorities and Local Councils - approve their part of the route, meaning one refusal or delay prevents access to the entire corridor.

The CCA industry recognises the progress made by the Victorian (Heavy Vehicle Structural Assessment Permit System - HVSAPS) and Tasmanian Governments (Heavy Vehicle Access Management System - HVAMS) to streamline how HV's gain access to the road network through these digital/automated systems. However, in the absence of the successful implementation of a true national approach – such as the NAAS - significant delays and costs will continue to be incurred.

Case Study: 19-Month Permit Delay

One CCAA operator sought a routine PBS truck-and-dog access permit for a short quarry-to-plant route involving both council and state roads. Although the vehicle type was already approved on similar routes, the approval process took 19 months.

The delay was driven by repeated requests for additional information from both the council and state road authority. Each time new information was sought, the clock restarted, meaning the operator endured multiple full assessment cycles for near-identical material. Misaligned requirements between agencies and staff turnover added further delay.

During this period, the operator was forced to use smaller non-PBS vehicles at higher cost, doubling trip numbers and reducing quarry and plant productivity. The case highlights how fragmented, sequential permitting and “reset-on-request” administration can turn an otherwise routine access application into a multi-year process, with avoidable cost and network impacts.

2.2.2 Outdated or incomplete PBS network mapping

Australia now operates a two-speed productivity system in relation to PBS access, mass limits and the broader regulatory environment that governs construction-materials transport. This divergence is not driven by differences in freight demand or vehicle capability, but by differences in state policy settings, risk appetite, technical capability and willingness to modernise access frameworks.

The leading states - NSW, WA, Victoria, South Australia and Tasmania - have embraced the PBS and high-productivity HV (HPHV) frameworks as a central pillar of their freight strategies. These jurisdictions have:

- **Expansive, well-defined PBS and HPHV networks.**
These states have progressively opened key freight corridors, quarries, industrial precincts and metropolitan connectors to PBS vehicles. Many of these networks extend deep into first- and last-mile routes and are updated regularly based on asset condition, traffic patterns and emerging freight needs.
- **Telematics-supported higher mass schemes.**
Programs such as the NSW Safety, Productivity and Environment Construction Transport Scheme (SPECTS) and the WA Accredited Mass Management Scheme (AMMS) enable HML under clear, consistent conditions. Telematics and OBM systems provide assurance to road managers and regulators, allowing productivity improvements without compromising safety or asset integrity.
- **Transparent and consistent assessment processes.**
These states use structured, repeatable and engineering-based assessment methods. Operators understand the criteria, timelines and evidence required. This reduces uncertainty, limits delays and encourages investment in PBS and HPHV vehicles and safety technologies.
- **Targeted first-/last-mile upgrades.**
State investment programs have increasingly focused on the short road segments that unlock access to quarries, batch plants, ports and construction hubs. These targeted upgrades generate significant productivity gains because they remove bottlenecks that previously rendered whole corridors unusable.

As a result, operators in these states enjoy greater regulatory certainty, higher productivity, fewer truck movements per tonne delivered and stronger incentives for fleet modernisation.

Example of a national outlier – Queensland

In contrast, Queensland has one of the most constrained PBS CML and HML and restricted first- and last-mile networks. This is a result of several complicated factors – including higher rainfall and higher risk of pavement damage, however regulatory and institutional settings have not been able to address this nor keep pace with other states.

Key issues include:

- **Limited GML and HML access.**
Queensland offers fewer HML and concessional schemes compared with NSW, WA and Victoria. Many HV routes remain restricted to GML, forcing more truck trips to move the same volume.

- Limited first- and last-mile access.
Networks vary significantly across Councils boundaries, and many first- and last-mile links remain unassessed or closed. The result is a patchwork of access rules that undermine route reliability.
- Risk-averse decision-making.
Access decisions often emphasise perceived rather than demonstrated engineering risk. For example, small mass increases are assumed to have significant impacts and raise rollover or infrastructure risk, despite PBS standards demonstrating high stability, especially with ESC/RSC. The real safety risk is additional truck movements and restricting mass forces more trips, increasing traffic exposure and congestion. Engineering evidence shows PBS vehicles at slightly higher masses remain safe and road-friendly.
- Lack of construction-sector schemes.
Queensland has no equivalent to NSW's SPECTS or WA's AMMS. Without a vehicle–network–telematics framework designed specifically for construction-materials transport, operators must rely on ad hoc permit processes that are slow and unpredictable.

This divergence constrains national productivity because construction supply chains do not operate within state borders - quarries, depots and markets often span multiple jurisdictions. When a single state persists with restrictive or outdated access settings, the entire multi-state network becomes less efficient.

Further PBS HML maps are frequently incomplete or not updated in line with freight demand. Key quarry or batch plant routes remain unassessed or restricted, meaning a road only metres from a state network may be blocked despite meeting engineering requirements.

2.2.3 Inefficient road funding and budget allocation policies

Australia's current heavy-vehicle charging framework is built around the PAYGO (Pay-As-You-Go) model. Under PAYGO, heavy-vehicle charges - registration fees and the fuel-based Road User Charges - are set to recover the historic, average expenditure that state and territory governments make on their roads.

However, PAYGO has two major structural limitations:

1. It recovers *past* expenditure rather than funding current or future needs thereby ignoring current and future freight pressures and typically underestimates the investment needed for future demand.
2. It distributes revenue only to state and territory governments, not to Local Governments.

This is a critical flaw for the construction-materials sector, because Local Governments maintain most of the roads that the CCA freight task uses - including quarry access roads, connector streets, industrial precinct roads, batch plant approaches and links into construction sites.

Under PAYGO, Local Governments receive none of the heavy-vehicle charges generated by the vehicles operating on their roads. Instead, Councils rely on:

- General rates revenues;
- Developer contributions;

- Ad hoc road user agreements;
- State funding programs, and
- Federal Grants (eg Financial Assistance Grants or FAGs).

However, these grants are not linked to heavy-vehicle use. They are formula-based, pooled funding arrangements that must cover a wide range of local services (waste, libraries, parks, community facilities, planning services, etc.). Only a fraction is available for roads - and even then, it is not tied to freight intensity or road wear from heavy vehicles.

This means Local Governments who host quarries, batch plants or high-density construction areas must maintain some of the most heavily used freight roads in the country, have no access to PAYGO heavy-vehicle charge revenue. The consequence is that CCA industry operators are often called upon to fund both own-user and multi-user roads that service quarries and the network – resulting in a ‘double dip’ contribution of the industry (i.e road users pay Local Government road user charges plus State Government registration charges plus Federal Government Road User Charges).

This structural misalignment produces several consequences:

- Chronic underfunding of roads with the highest freight intensity.
Local roads bearing hundreds of heavy-vehicle movements per day receive no additional funding despite being central to the national construction supply chain.
- Double charging of operators and industry.
Because PAYGO does not support local roads, Councils increasingly impose levies, access charges, maintenance contributions or intersection upgrades - meaning operators pay PAYGO charges *and* local charges.
- No reward for jurisdictions that enable productivity.
States or Councils that expand PBS or higher-mass access do not receive additional road funding, even though they may reduce network-wide costs by enabling fewer truck trips.
- No differentiation between high- and low-performing fleets.
A modern PBS truck with OBM, ESC, RSC and road-friendly suspension pays the same charges as an older, less safe, more road-damaging vehicle. PAYGO contains no mechanism to reward safer, more productive, lower-impact fleet investment.
- A disconnect between charges and the roads used.
Construction-materials vehicles overwhelmingly use local roads, yet PAYGO funds only state-managed networks.

There is also cost recovery misalignment – where state road agencies at times deny certain HV combinations access to certain roads due to an inadequate cost recovery. If states continue to make access decisions based on these fundamentals, there is a strong argument for a phased transition toward a Mass–Distance–Location (MDL) charging framework enabled by telematics, data-sharing and strong governance structures.

2.2.4 *First- and last-mile restrictions that block access to otherwise suitable corridors*

Councils capability to assess and grant first- and last-mile access for heavy vehicles varies widely across Australia. Some Local Governments have engineering expertise, pavement data and bridge assessments; many do not. Without consistent tools or nationally standardised assessment methods, Councils rely on different criteria, assumptions and risk thresholds when making decisions. This results in substantial inconsistency: neighbouring Councils with similar road conditions often reach opposite conclusions on the same PBS vehicle. These inconsistencies undermine the intent of PBS, which was designed to provide a uniform, evidence-based access framework across Australia.

Because Councils often lack asset information or heavy-vehicle assessment capability, uncertainty frequently results in conservative decisions. Access may be restricted or refused not due to demonstrated safety concerns, but because Councils cannot confidently assess the risk. Delays are also common, with some applications waiting weeks or months for decisions on local roads that carry heavy vehicles every day.

Councils often decline access not because PBS vehicles are unsafe, but because they cannot quantify the risk. This creates systemic chokepoints. Declared state high-productivity corridors provide no benefit if the 500 metres from a quarry gate to the arterial remains restricted.

The consequence is that PBS vehicles - despite being safer, more stable and more road-friendly - are frequently unable to access short but essential local-road links that determine whether entire freight corridors are usable.

This mismatch between modern vehicle performance and outdated access processes is now one of the most significant constraints on productivity within the CCA sector.

Governments have begun to recognise these structural issues, and several initiatives are underway to support Local Governments and reduce first- and last-mile barriers, for example:

- Austroads now delivers national training programs to build local-government capability in heavy-vehicle assessment and is developing standardised engineering tools to support more consistent decision-making.
- The NHVR has established a Road Manager Support Program that provides Councils with technical advice, training, and digital bridge and pavement assessment tools to assist with PBS and higher-mass applications.
- State governments are also investing in targeted first- and last-mile upgrades through programs such as Fixing Country Roads (NSW), the Heavy Vehicle Safety and Productivity Program, and WA's network-tiered AMMS framework.
- The development of the NAAS is a further step toward modernising and standardising access assessments nationally.

These initiatives represent positive progress, but they remain early-stage and uneven across jurisdictions. Significant capability gaps persist, and without a consistent national framework, local-road assessments will continue to be a major bottleneck for productive, low-impact PBS operations.

2.2.5 *Planning-system operating-hour curfews that compress freight into inefficient peak-hour windows*

A significant productivity barrier for the CCA industry - one not captured in current heavy-vehicle regulatory frameworks - is the prevalence of stringent operating-hour restrictions imposed through State and Local Government planning and Development Assessment (DA) processes.

These restrictions commonly limit quarry, batching plant and depot operations (eg maintenance and HV loading) to windows such as 7:00am - 4:30pm, with strict constraints on HV movements outside those hours.

For the CCA sector, these limits impose substantial inefficiencies:

- Construction sites often commence work well before 7am, yet concrete and aggregates cannot be delivered until sites are already active.
- Peak-hour congestion compresses freight into the least efficient times of day, increasing trip times and fuel consumption.
- Batching plants must complete all deliveries within a narrow window, creating artificial peaks that exacerbate traffic impacts.
- Quarries and cement depots are forced to stack demand into mid-morning periods, reducing throughput.
- Operators lose significant working hours to regulatory curfews rather than genuine safety or amenity concerns.

Crucially, these planning restrictions operate independently of HV access regimes, meaning that even if PBS access, higher mass limits or NAAS automation is delivered, the productivity benefit is muted if trucks are allowed to operate only within narrow local-government-imposed windows.

This is an especially acute issue for construction materials because:

- Concrete has a finite working life and must be delivered at precise times;
- Major infrastructure projects frequently schedule early starts to manage traffic and safety;
- Construction supply chains depend on predictable, early-morning mobilisation;
- Aggregate and cement supply is typically required ahead of the main daily construction window, and
- Most noise-related impacts stem from site operations, not vehicle propulsion systems, meaning EV trucks do not eliminate the issue.

In many cases, planning-hour restrictions are more constraining than transport regulations themselves, yet they are rarely considered in national freight reform discussions.

While Councils impose these limits to balance industry operations with community amenity, current blanket rules often fail to distinguish between:

- Heavy industrial noise versus truck arrival noise;

- Low-impact early-morning movements versus full production activity, and
- Sites adjacent to industrial zones versus sensitive residential areas.

The result is a rigid system that does not reflect modern vehicle technology, improved safety, or the essential nature of the construction-materials supply chain.

2.2.6 *Weak mass-limit enforcement*

CCAA is also concerned that inadequate enforcement of mass limits creates a commercial disadvantage for accredited operators who invest in PBS vehicles, OBM systems and higher compliance standards. These fleets carry higher operating costs, while non-accredited operators can exploit weak enforcement settings and gain an unfair commercial advantage.

This dynamic not only erodes the business case for maintaining high compliance standards, but also disincentivises operators from investing in higher-productivity heavy vehicles (HPHVs), undermining the safety and efficiency outcomes governments seek to promote through PBS and modern access frameworks.

2.2.7 *A lack of nationally consistent construction-materials access frameworks like SPECTS*

Only a small number of jurisdictions - most notably New South Wales and Western Australia - have developed sector-specific access frameworks tailored to the operational needs of the construction-materials industry.

In NSW, SPECTS provides a structured, transparent framework for construction-materials vehicles that integrates defined vehicle standards, concessional mass limits, telematics requirements and pre-approved networks. In Western Australia, the AMMS delivers a similar level of certainty by combining mass concession levels, road-friendly suspension requirements and clear network tiers based on matching vehicle configurations to defined asset capability.

These schemes enable safer, more productive PBS vehicles to operate at their engineered potential on pre-identified networks where asset conditions, vehicle standards and compliance expectations are well aligned. They dramatically reduce administrative burden and provide operators with predictable, repeatable access outcomes.

However, no equivalent national scheme exists. Other jurisdictions rely on older, fragmented or prescriptive access processes that were not designed with PBS vehicles in mind. In these states, access decisions occur on a route-by-route, councils-by-councils basis, creating uncertainty, delays and inconsistent outcomes for the same vehicle types. Without a sector scheme, there is no mechanism to align vehicle performance, mass limits, telematics, and network planning in a way that reflects the high-frequency, short-haul nature of the CCA task.

The absence of nationally consistent construction-materials schemes means operators face significantly different rules, mass limits and productivity outcomes depending on the state they operate in. A PBS truck-and-dog combination may operate efficiently at higher mass limits on a defined SPECTS or AMMS network, yet face lower mass, reduced access or lengthy permit processes in Queensland or South Australia. This fragmented approach suppresses national productivity, reduces regulatory certainty, and undermines the intent of the PBS framework.

2.2.8 *A lack of planning protection of key transport corridors*

A growing structural risk to construction-materials freight is the lack of effective planning protection for key transport corridors and industrial precincts.

In many jurisdictions, residential and mixed-use development is being permitted to encroach on established freight routes, quarries, depots and port-related precincts. This intensification of sensitive land uses close to heavy-vehicle corridors inevitably leads to increased community complaints about noise, dust, safety and truck numbers, which in turn places pressure on governments and Councils to restrict operating hours or curtail access. Over time, this dynamic erodes the social licence for freight operations that long pre-date surrounding development.

Recent Victorian policy work¹ explicitly acknowledges this challenge. Land-use and transport integration guidance emphasises the need not only to locate housing and jobs close to transport, but also to protect existing and planned transport infrastructure from the impacts of surrounding development, including freight routes and terminals.

Similar pressures are evident in Queensland, particularly in South East Queensland (SEQ), where rapid population growth and housing development are occurring along or adjacent to key freight routes and industrial areas.

Strategic documents such as *Connecting SEQ 2031* and broader SEQ transport and growth visions recognise that accommodating growth will require careful integration of housing and freight, yet in practice Local Government's continue to make planning decisions that inevitably lead to increased objections to truck movements.

Without stronger, proactive planning protection of freight corridors and construction-materials precincts - through buffers, compatible zoning, and explicit freight overlays - these trends will progressively constrain operating hours, limit route options and undermine the viability of higher-productivity heavy vehicles. For a sector that depends on fixed quarries and batch plants and must move high volumes daily, clearer national and state-level planning policies to identify, protect and future-proof key freight routes are essential to maintaining both productivity and social licence.

2.2.9 *Absence of incentives for Councils to pursue access improvements*

Local Governments carry a disproportionate share of responsibility in Australia's freight access system. They are expected to assess, consent to and manage the impacts of HV movements on their local road networks, yet they receive no direct funding or financial benefit when granting PBS access. Councils therefore carry the risk, but not the reward.

Council-managed roads are essential to the CCA freight task, forming the first- and last-mile links between quarries, batch plants, cement depots and construction sites. These roads experience high volumes of HV's despite limited funding support with PAYGO revenues flowing mainly to State governments, leaving Councils without the resources needed to maintain or upgrade the very roads that support construction activity.

At the same time, Councils face strong community and political pressure relating to truck movements, noise and perceived safety concerns and in some jurisdictions also have veto over projects through control of DA's. Without standardised assessment tools, reliable asset data or clear incentives, Councils often default to conservative decisions on quarry approvals and/or

¹ [The Victorian Freight Plan 2025-30: Victoria Delivers](#)

operating hours and in road funding programs. Uncertainty becomes a barrier to approval, even when PBS/ HPHV vehicles are demonstrably safer and more road-friendly.

Importantly, Councils do directly benefit from the outcomes that efficient construction-materials transport enables. Timely, predictable and productive supply of aggregates, cement and concrete supports the delivery of local infrastructure, including roads, drainage, community facilities and housing developments. Efficient materials transport shortens project timelines, reduces disruption and supports the economic growth Councils are tasked with enabling.

However, these benefits are not linked to the access decision itself. Councils receive no direct financial return for supporting more productive freight operations.

This misalignment - Councils bearing the risk while communities who receive aggregates, cement and concrete (both inside and outside of the Local Government Area where these materials originate) enjoy the downstream benefits - creates a structural barrier to PBS and access. Productivity reforms must therefore include measures that support Councils with funding, tools and incentives so their decisions better reflect the broader economic and community benefits of enabling modern, safe and efficient PBS vehicles.

3.0 THE COMMONWEALTH'S ROLE IN IMPROVING HV ACCESS

The barriers facing construction-freight productivity - fragmented rules, inconsistent access, misaligned funding, and duplicated assessment processes - closely resemble the structural challenges addressed through Australia's earlier National Competition Policy (NCP) reforms. These are system-wide failures that no single State or Local Government can resolve independently. They require national coordination, clear policy direction, and incentive structures that align the interests of all levels of government.

The Commonwealth is uniquely positioned to lead these reforms because it:

- Sets the overarching economic and competition policy framework;
- Funds major national road infrastructure;
- Administers federal grants to Local Governments;
- Has the authority to modernise national charging and pricing systems, and
- Is responsible for productivity, housing supply, and economic performance across jurisdictions.

While states manage the road networks and Councils manage most of the first and last-mile connections, the Commonwealth is the only entity capable of integrating these components into a coherent national system.

To address the systemic constraints facing the construction-materials freight task, the Commonwealth should drive a modern, NCP-informed national reform program focused on the following.

3.1 National adoption of the National Automated Access System

The NAAS represents the most significant modernisation opportunity for HV access since the introduction of PBS. NAAS standardises the *process* of access assessment by applying

nationally consistent engineering logic, automating routine decisions, and integrating asset and telematics data into a single assessment engine.

To realise its full productivity potential, the Commonwealth should:

- fund its national deployment;
- mandate its adoption across all jurisdictions;
- ensure Councils have the tools, capability and data needed to use it effectively, and
- support the integration of bridge, pavement and telematics datasets into the platform.

NAAS would replace today's manual and inconsistent decision-making with a modern, data-driven, transparent system. This is essential to reduce delays, improve consistency and support evidence-based access outcomes.

3.2 A harmonised SPECTS like scheme for construction materials supply across States and Territories

While NAAS will modernise how access decisions are made, genuine national productivity requires aligning what rules those decisions are based on. The CCA industry has operational characteristics that make a uniform, sector-specific national framework essential.

Construction-materials transport is uniquely high-frequency, short-haul and time-critical. Vehicles may complete 15–25 trips per day from fixed quarries, batch plants and depots using the same local-road links millions of times per year. Unlike general freight, these origins and destinations cannot be relocated or rerouted around restrictions. Even small inconsistencies in access or mass limits lead to disproportionate increases in truck movements, project delays and congestion. Because construction materials cannot be stockpiled and are essential to housing and infrastructure delivery, inefficiency in this sector has direct national economic consequences.

The sector also has high PBS uptake, predictable operating patterns and strong telematics and compliance penetration, making it ideally suited for a structured, pre-assessed regulatory framework. Jurisdictions that have implemented dedicated construction-materials schemes - such as the NSW SPECTS and the WA AMMS - have demonstrated that aligning vehicle standards, network rules and mass limits delivers significant productivity and safety benefits while reducing administrative burden.

To overcome the current state-by-state inconsistency, the Commonwealth should establish a nationally consistent construction-materials access framework, which states would administer on their own networks.

This framework would align:

- PBS vehicle standards
- CML/HML
- Telematics and OBM requirements
- Access decision-making thresholds and methodologies.

A national framework would eliminate the counterproductive patchwork where a vehicle that operates safely and efficiently in one state faces lower mass limits, reduced access, or outright refusal in another. When combined with NAAS this framework would deliver predictable, evidence-based and nationally consistent access for operators investing in modern, safe and productive fleets.

A harmonised national approach acknowledges the unique characteristics of the construction-materials freight task and is critical to unlocking the next major wave of productivity in Australia's housing and infrastructure delivery pipeline.

3.3 Reform of HV pricing to a Forward-Looking Cost Base (FLCB) and adoption of Mass-Distance-Location charging

The Commonwealth should lead the transition to an FLCB model that:

- aligns charges with actual and future freight task demands;
- directs funding to where heavy-vehicle activity occurs, including local roads;
- recognises modern, high-performance vehicles, and
- enables long-term, sustainable funding for first- and last-mile infrastructure.

This is one mechanism to fix the fundamental misalignment between who uses the roads, who pays, and who maintains them.

Effort should also continue in evaluating the introduction of Mass-Distance-Location (MDL) charging as a fairer and more efficient mechanism to allocate the true costs of freight movements. MDL charging ensures that operators contribute in proportion to the mass they carry, the distance they travel, and the locations they impact - driving better investment signals and supporting sustainable funding of local and first- and last-mile infrastructure.

To this end, CCAA notes:

- The results of the National Heavy Vehicle National Pilot (NHVCP), which is testing different ways to charge heavy vehicles for road usage based on the weight of the vehicle and distance travelled (including the use of telematics to collect information) is now being analysed².
- The direction of national Infrastructure and Transport Ministers (Infrastructure and Transport Ministers Meeting) in charging the National Transport Commission to consult on a forward-looking cost base (FLCB) as an alternative way to set heavy vehicle charges.³

² <https://www.infrastructure.gov.au/infrastructure-transport-vehicles/transport-strategy-policy/heavy-vehicle-road-reform/national-heavy-vehicle-charging-pilot>

³

<https://www.ntc.gov.au/sites/default/files/assets/files/Heavy%20Vehicle%20Charges%20Consultation%202026-27.pdf>:

3.4 Local Government capability uplift

Some Australian Councils lack the technical and financial capacity to perform modern heavy-vehicle access assessments. The Commonwealth should role out consistent and well-resourced national initiatives that:

- Fund training, tools and technical support for asset managers;
- Support the acquisition of digital assessment systems and asset data;
- Strengthen Councils' ability to manage freight impacts in growing urban areas, and
- ILnk support to improved turnaround times and evidence-based decision-making.

Capability uplift reduces risk-aversion and enhances safety, efficiency and confidence in the system.

3.5 Incentive-based funding tied to access performance

The Commonwealth should provide states and Councils with clear, measurable incentives to improve access outcomes. This could include:

- Federal funding bonuses tied to expanded PBS HML networks and KPI's such as:
 - Kilometres of expanded PBS CML and HML network
 - Journey-time reliability
 - The proportion of the freight network that is mass-constrained
 - The number of structural bottlenecks restricting access.
- Targeted first-/last-mile infrastructure programs
- Performance benchmarks for timely access decisions
- Funding linked to adoption of NAAS and telematics-supported schemes.

Incentive-based reform is a proven NCP mechanism for aligning state and local decisions with national productivity objectives.

3.6 National planning alignment to protect freight corridors

The growing encroachment of sensitive land uses near established freight routes, quarries, batch plants and industrial precincts will progressively constrains operating hours, restrict access and erodes the social licence necessary for productive PBS and HPHV operations.

The Commonwealth should lead a nationally consistent planning framework that:

- Embeds freight-corridor protection into national urban-policy and housing-supply agreements.
- Links federal infrastructure and housing funding to freight-compatible land-use decisions.

- Requires states to map, protect and future-proof key construction-materials corridors.
- Supports buffer policies, freight overlays and land-use conflict mitigation tools.

This would ensure that the productivity and access reforms delivered through NAAS, PBS and FLCB/MDL charging are not undermined by local planning decisions.

4.0 BARRIERS TO AVAILABILITY OF EV TRUCK CHARGING INFRASTRUCTURE

Heavy battery-electric trucks are emerging but remain operationally challenging for the CCA industry. While CCAA supports decarbonisation and recognises the long-term role of zero-emission heavy vehicles, the CCAA industry – beyond cost and mass/payload tradeoffs, - faces unique charging constraints due to high fleet utilisation, very high trip frequency, fixed facility locations and tight delivery time requirements.

CCAA's views on the charging barriers are elaborated below.

4.1 Planning and zoning restrictions

Many quarries, concrete batch plants and cement depots operate on industrial sites with limited land availability, strict buffer zones and planning constraints. Current planning systems are not designed for large-scale heavy EV charging, which require:

- High-voltage grid connections.
- Sufficient transformer capacity.
- Dedicated charging bays big enough for PBS trucks.
- Operational space for queuing and circulation.

Most local zoning frameworks do not yet contemplate these footprints, creating lengthy approval processes and uncertainty.

4.2 Grid connection approvals and energy regulations

High-capacity DC fast chargers for heavy trucks require grid upgrades that at times trigger:

- Environmental approvals.
- Distribution network service provider (DNSP) assessments.
- Lengthy connection studies and augmentation costs.

For many sites, especially regional quarries, required upgrades are technically feasible but financially prohibitive without government co-investment.

4.3 Practical barriers to installation and operation

4.3.1 Lack of space at production sites

Batch plants and quarries already operate under tight spatial optimisation. Unlike depots or logistics hubs, CCA sites cannot easily dedicate large areas for EV infrastructure without reducing stockpile space, raw materials handling, truck circulation or safety margins.

4.3.2 High vehicle utilisation unsuitable for long charge times

CCA trucks often complete up to 25 trips per day, with rapid turnaround times and minimal dwell periods. Existing heavy EV charging technologies cannot support these utilisation rates without:

- Multiple high-capacity chargers.
- Extensive grid infrastructure.
- Battery sizes that significantly reduce payload.

4.3.3 Route-based charging is not practical for CCA

CCA truck movements are short-range and repetitive. They do not stop at long-haul rest stations or freight hubs. Therefore, public chargers along highways do not suit:

- Agitators delivering concrete.
- Quarry trucks hauling aggregates.
- Cement bulk tankers distributing to metropolitan plants.

A lack of fit-for-purpose metropolitan industrial charging sites is a primary barrier.

4.4 Mismatch between costs and who benefits

Charging infrastructure requires significant capital investment at sites operated by private companies, but the public benefit - reduced emissions and noise - is much broader. Without government co-funding or tax incentives, the business case remains weak.

4.5 Uncertain technology pathway

For many construction-materials applications:

- hydrogen,
- battery swapping,
- trolley assist, or
- hybrid solutions,

may be more suitable than plug-in battery-electric trucks due to weight, power demands, and duty cycles. Premature regulatory settings risk locking industry into suboptimal technologies.

4.6 Risk of stranded assets

Given rapid technology change, investing in EV chargers now may result in stranded assets if:

- Charging standards evolve (i.e. today's charger types become incompatible with future truck technologies or plug standards).
- Megawatt charging becomes universal (i.e. high-power MCS systems replace current fast-charging infrastructure and make it obsolete).
- Hydrogen becomes dominant for heavy fleets (i.e. operators invest in EV hardware only to find future fleets shift to hydrogen fuel-cell technology instead).

Industry prefers coordinated national planning rather than piecemeal site-by-site investment.

5.0 CURFEWS FOR EV TRUCKS

Current curfew settings do not differentiate between electric and diesel heavy vehicles – that is, under both the HVNL and Local Government planning and traffic regulations, EV trucks are treated the same as all other heavy vehicles and are subject to identical curfews. While the Productivity Commission is exploring whether EVs should receive different curfew treatment, no such provisions exist today.

Given that most noise and amenity impacts in the construction-materials heavy vehicle transport sector arise from loading, unloading, agitator operation and other site activities - not solely from engine noise – the noise and community benefits of an EV curfew exemption are likely to be variable and dependent on the operating circumstances and activity (eg driving or loading/or unloading).

Introducing curfew exemptions or increased curfew flexibility for EV trucks could deliver tangible benefits for both industry and the community.

For industry, extended operating windows would improve fleet utilisation, reduce transit times by enabling movements during low-congestion periods, and provide a practical incentive for operators to invest in EV technology.

Hence, greater operating flexibility may be one of the most meaningful commercial levers available to accelerate EV uptake in the construction-materials sector.

The community would also benefit from EV curfew flexibility where quieter drivetrain performance leads to reduced noise impacts during early-morning or late-evening periods.

Operating outside standard hours can also ease peak-hour congestion, improve safety outcomes through fewer heavy vehicles mixing with commuter traffic, and reduce emissions in densely populated areas.

However, to maximise overall productivity and maintain fairness across the sector, any EV curfew flexibility should be complemented by a broader review of curfew settings for compliant internal combustion engine (ICE) fleets, ensuring curfew policy is aligned with actual noise impacts and wider community amenity considerations.

6.0 CONCLUSION

To support improved heavy-vehicle (HV) productivity and decarbonisation, we recommend the Commission critically examine the costs and benefits of the following reforms:

1. A nationally harmonised construction-materials access framework that provides enhanced CML and HML access on pre-approved gazetted networks for PBS vehicles that meet certain vehicle configuration standards (like the NSW SPECTS and WA AMMS regimes).
2. Different cost recovery and cost allocation approaches such as:
 - a Forward-Looking Cost Base (to ensure heavy vehicle road user charges reflect the efficient future cost of building, operating and maintaining the road network), and
 - Mass-Distance-Location charging (to ensure costs are allocated fairly to users based on the impact they impose on different parts of the network,

as potential pathways to more sustainable funding stream to enable improved first- and last-mile Local Government access, and essential State Government mapping, evaluation and upgrades of the PBS CML and HML network.

3. A targeted Commonwealth capability program for Local Governments, including digital tools, asset data, bridge and pavement assessment systems, to support safe, timely and evidence-based HV road access decisions.
4. A targeted, Commonwealth incentive program that links State, Territory & Local Government road funding to agreed KPI's to drive general performance and accountability.

KPI's could include:

- Kilometres of expanded PBS CML and HML network.
 - Journey-time reliability.
 - The proportion of the freight network that is mass-constrained.
 - The number of structural bottlenecks restricting access.
5. Strengthened HV mass compliance and enforcement activity to ensure accredited, PBS fleets are not disadvantaged and are rewarded for investing in higher safety and productivity HV's.
 6. A stronger national approach to protecting key freight and construction-materials transport corridors - including the use of Commonwealth funding conditions, national planning frameworks, Infrastructure Australia assessment requirements, and coordinated state-federal governance - to prevent incompatible land-use encroachment and ensure long-term access for high-productivity heavy vehicles.
 7. A nationally consistent HV curfew policy that incentivises the adoption of EV HV's whilst promoting greater operating hour flexibility for non-EV PBS HV's to improve safety, reduce peak-hour congestion exposure and support the reliable delivery of construction materials.
 8. A targeted, Commonwealth program that supports HV charging infrastructure planning and costs.

In relation to the NAAS, CCAA believes that this represents the most significant modernisation opportunity for HV access since the introduction of PBS. To realise its full productivity potential, the Commonwealth should:

- Fund its national deployment.
- Mandate its adoption across all jurisdictions.
- Ensure Councils have the tools, capability and data needed to use it effectively.
- Support the integration of bridge, pavement and telematics datasets into the platform.



Attachment 1: Australian Road Freight Transport – National and Jurisdictional Metrics (All Commodities vs Construction-Materials Sector)

AUSTRALIAN ROAD FREIGHT TRANSPORT (ALL VS CCA INDUSTRY)									
	QLD	NSW	VIC	TAS	SA	NT	WA	TOTALS	
Total road freight transport (all commodities)	Annual trailers	5,055,681	6,042,728	4,645,434.48	709,414.53	1,425,384.64	203,814.61	4,770,479.32	22,852,936
	Annual tonnes	98,580,869	121,600,672	92,278,274	13,997,706	30,652,553	3,986,519	104,953,792	466,050,385
	Tonne kilometres (billion t kms)	25.55	24.75	14.51	2.71	6.54	1.50	30.75	106.3
	Tonnes/trailer (average)	16.3	16.9	16.5	16.7	16.9	14.8	16.9	16.4
	Avg Trip Distance (km) (average)	144.4	104.8	83.8	99.5	101.0	154.8	147.9	119.5
	Avg Trip Duration (hrs) (average)	1.6	1.2	1.0	1.1	1.2	2.2	1.6	1.4
	Cost per payload tonne (\$) (average)	\$ 54.54	\$ 36.76	\$ 26.30	\$ 39.82	\$ 30.66	\$ 82.49	\$ 41.32	\$ 44.55
	Cost per tonne km (\$) (average)	\$ 0.38	\$ 0.35	\$ 0.38	\$ 0.38	\$ 0.39	\$ 0.43	\$ 0.39	\$ 0.38
Total transport costs (\$)	\$ 2,698,907,482	\$ 2,525,813,332	\$ 1,456,155,721	\$ 297,111,881	\$ 593,587,827	\$ 105,670,530	\$ 3,300,406,952	\$ 10,977,653,725	
CCA sector only (clinker, cement, rock, sand, gravel & concrete commodities only)	Annual trailers	2,022,394	3,286,747	2,080,274.13	175,877	463,663.01	125,347.71	734,768.68	8,889,072
	Annual tonnes	41,517,152	67,572,576	42,535,712	3,835,877	9,738,726	2,568,172	15,140,055	182,908,270
	Tonne kilometres (billion t kms)	7.79	5.18	2.20	0.61	1.91	0.97	3.47	22.1
	Tonnes/trailer (average)	20.5	20.4	20.3	21.6	20.4	21.1	20.4	20.7
	Avg Trip Distance (km) (average)	91.7	76.6	49.4	79.5	97.9	185.1	110.2	98.6
	Avg Trip Duration (hrs) (average)	1.1	0.9	0.6	1.0	1.2	2.6	1.2	1.2
	Cost per payload tonne (\$) (average)	\$ 16.62	\$ 13.49	\$ 8.64	\$ 9.86	\$ 12.57	\$ 19.69	\$ 15.12	\$ 13.71
	Cost per tonne km (\$) (average)	\$ 0.23	\$ 0.24	\$ 0.27	\$ 0.25	\$ 0.22	\$ 0.17	\$ 0.20	\$ 0.23
Total transport costs (\$)	\$ 689,963,087	\$ 911,558,853	\$ 367,546,025	\$ 37,806,364	\$ 122,379,407	\$ 50,575,278	\$ 228,984,359	\$ 2,408,813,373	
CCA/Total	Annual trailers	40%	54%	45%	25%	33%	62%	15%	39%
	Annual tonnes	42%	56%	46%	27%	32%	64%	14%	39%
	Tonne kilometres (billion t kms)	30%	21%	15%	23%	29%	65%	11%	21%
	Total transport costs (\$)	26%	36%	25%	13%	21%	48%	7%	22%
CCA +/- % (compared to total averages)	Tonnes/trailer (average)	26%	20%	23%	29%	21%	42%	21%	26%
	Avg Trip Distance (km) (average)	-36%	-27%	-41%	-20%	-3%	20%	-25%	-19%
	Avg Trip Duration (hrs) (average)	-35%	-23%	-35%	-15%	2%	15%	-23%	-16%
	Cost per payload tonne (\$) (average)	-70%	-63%	-67%	-75%	-59%	-76%	-63%	-68%
	Cost per tonne km (\$) (average)	-39%	-31%	-28%	-34%	-44%	-60%	-48%	-41%

Source: CSIRO Transport Network Strategic Investment Tool (2025 data)

**ATTACHMENT B – CCAA sub to NTC re Mass, Dimension and Loading National
Regulation Amendment**

19 January 2026

National Transport Commission
Level 3/600 Bourke Street
Melbourne VIC 3000

Submitted via: enquiries@ntc.gov.au

NTC Consultation draft Heavy Vehicle (Mass, Dimension and Loading) National Regulation Amendment and Explanatory Document

Dear Commissioners

Cement Concrete & Aggregates Australia (CCA) welcomes the opportunity to comment on the National Transport Commission's consultation draft of the Heavy Vehicle (Mass, Dimension and Loading) National Regulation Amendment and associated Explanatory Document.

CCA is the peak body representing Australia's heavy construction materials industry, including cement manufacturing, concrete production and quarrying operations. Our sector underpins Australia's housing and infrastructure delivery and is characterised by high-density, mass-constrained freight tasks, dynamic loads and time-critical deliveries. As a result, the practical operation of mass and dimension regulation has a direct and material impact on safety, productivity, decarbonisation outcomes and construction costs borne by the wider community.

What CCA Supports

CCA **strongly supports** the intent of the NTC's reform agenda to modernise heavy vehicle regulation and reduce unnecessary regulatory complexity. CCA supports:

- 1. Alignment of General Mass Limits (GML) with Concessional Mass Limits (CML)**
Aligning baseline GML axle and group mass limits with existing CML settings appropriately reflects the safety and engineering capability of the modern heavy vehicle fleet and removes unnecessary reliance on NHVAS Mass Management accreditation for routine operations.
- 2. Increase in Prescriptive Length to 20 Metres for Rigid Truck and Dog Combinations**
Increasing general access length from 19 metres to 20 metres has the potential to deliver significant productivity, safety and network efficiency benefits by mainstreaming configurations currently reliant on PBS Level 1 approvals.
- 3. Extension of Euro VI Steer Axle Concessions to Road Trains and Twin-Steer Vehicles**

Extending the existing 0.5-tonne steer axle concession removes a clear disincentive to fleet renewal and improves safety outcomes for regional and remote supply chains.

4. **Reform of Tag Trailer Tow Mass Ratios**

Replacing the restrictive 1:1 tow mass ratio with the proposed 1:1.3 ratio better reflects engineering reality and improves the efficient movement of plant and equipment across construction and quarrying operations.

What CCAA Does Not Support

Notwithstanding this broad support, CCAA **does not support** several elements of the draft Regulation as currently proposed:

1. **Removal of the 1-Tonne Tri-Axle Mass Transfer Allowance (1TMTA)**

Construction materials freight involves inherently dynamic loads, including fluid concrete and shifting aggregates. The 1TMTA functions as a critical compliance tolerance rather than a productivity concession. Its removal would convert the proposed 21-tonne tri-axle limit into a hard cap, forcing systematic under-loading to manage compliance risk and negating the intended productivity benefits of the mass increase.

2. **Failure to Explicitly Link 20-Metre Length to Tier 1 Bridge Formula Mass Limits**

Length without corresponding mass delivers no benefit for density-constrained freight and would preserve reliance on Notices or permits, undermining the objective of regulatory simplification.

3. **Insufficient Provision for Zero-Emission Heavy Vehicles**

The proposed 0.5-tonne Euro VI concession is materially insufficient to offset the 2.5–3.0-tonne tare weight penalty associated with battery-electric heavy vehicles and renders zero-emission construction vehicles commercially unviable.

4. **Exclusion of 20-Metre B-Doubles from the Current Amendment**

“Pocket” B-doubles are critical to urban cement and construction supply and should not be deferred to a future reform package.

5. **Ongoing Ambiguity Regarding Tri-Drive Configurations**

Regulatory ambiguity that effectively excludes tri-drive rigid trucks from simplified access frameworks penalises safer, high-traction vehicles used in quarry environments.

Changes Requested by CCAA

CCAA requests that the final Regulation:

1. Retain the **1-Tonne Tri-Axle Mass Transfer Allowance** alongside the new 21-tonne GML tri-axle limit.
2. Explicitly link **20-metre rigid truck and dog combinations to a 50.5-tonne GCM** where Tier 1 Bridge Formulae are satisfied.
3. Introduce a **Zero-Emission Heavy Vehicle mass framework**, including:
 - a minimum 2.0-tonne GVM concession;
 - steer axle limits of 8.0 tonnes (single) and 13.0 tonnes (twin); and
 - full harmonisation with the 2.55 m vehicle width standard
4. Include **20-metre B-doubles** in the current amendment package.
5. Explicitly include **tri-drive axle configurations** within prescriptive 20-metre access arrangements.

For clarity, **Attachment 1** provides a concise summary of the productivity and cost impacts across the cement, concrete and aggregates (CCA) sectors, supported by national freight task data set out in **Attachment 2**, and CCAA's full technical submission is provided overleaf.

CCAA considers these amendments a generational opportunity to improve freight productivity, reduce construction costs and support decarbonisation of the heavy vehicle fleet. These benefits will only be realised if the final Regulation reflects the operational realities of mass-constrained and dynamic construction materials freight.

Should officials wish to discuss this matter, please contact CCAA's Industry Policy Director, Mr David Rynne via david.rynn@ccaa.com.au and

Yours sincerely

MICHAEL KILGARIFF
Chief Executive Officer

About CCAA

CCAA is the voice of the \$15 Billion heavy construction materials industry representing cement manufacturers, concrete suppliers, and extractive operators throughout Australia.

Our members range from large global companies to SMEs and family operated businesses and are engaged in the quarrying of sand, stone and gravel, the manufacture of cement and the supply of pre-mixed concrete.

These businesses service local, regional, and national construction and infrastructure markets to meet Australia's building and construction needs through the provision of roads, railways, bridges, ports, airports, hospitals, schools, and footpaths.

Full CCAA submission

Consultation draft Heavy Vehicle (Mass, Dimension and Loading) National Regulation Amendment and Explanatory Document

1. Executive Summary

This submission assesses the National Transport Commission's consultation draft of the Heavy Vehicle (Mass, Dimension and Loading) National Regulation Amendment through the operational and economic lens of Australia's cement, concrete and aggregates (CCA) sector.

Construction materials freight is fundamentally different from general road freight. As shown in **Attachment 2**, the CCA sector accounts for approximately 39 per cent of national road freight tonnes but only 21 per cent of tonne-kilometres, reflecting short-haul, mass-constrained operations with high payload intensity and no practical opportunity for backloading. As a result, CCA vehicles almost always "weigh out" before they "cube out", meaning even modest changes to mass limits, tolerances or tare weight have disproportionate impacts on productivity, compliance risk and cost-to-serve.

CCAA supports the NTC's objective to modernise heavy vehicle regulation and reduce unnecessary regulatory complexity. In particular, the alignment of General Mass Limits (GML) with Concessional Mass Limits (CML) and the proposed increase in prescriptive length to 20 metres represent a significant opportunity to improve productivity across all three CCA commodities.

If implemented correctly, the reforms deliver clear, quantifiable payload gains. As summarised in **Attachment 1**:

- **Aggregates:** linking 20-metre truck and dog combinations to Tier 1 Bridge Formula mass limits (50.5 tonnes GCM) delivers a **net payload increase of approximately 7.5 tonnes per trip** (around **+28 per cent**), reducing transport costs by more than **20 per cent** and materially lowering truck movements.
- **Cement:** aligning GML with CML for B-double and road-train configurations delivers a **net payload gain of approximately 2 tonnes per trip** (around **+5 per cent**), directly reducing cost-to-serve for urban and regional cement supply.

Note, for cement transport, aligning GML with existing CML settings removes unnecessary reliance on mass accreditation for routine operations. While large operators already operating under CML will see limited direct payload or cost impacts, the reform materially benefits smaller and non-accredited fleets and simplifies compliance across the sector.

- **Concrete:** increased axle mass allowances support a **net payload gain of approximately 1 tonne per trip** for conventional diesel agitators (around **+6 per cent**), improving fleet efficiency without increasing vehicle numbers.

These outcomes directly support national objectives for productivity, safety, congestion reduction and emissions abatement.

However, the draft Regulation also contains several critical flaws that risk undermining these gains for the construction materials sector.

Most significantly, the proposed **removal of the 1-Tonne Tri-Axle Mass Transfer Allowance (1TMTA)** converts the new 21-tonne tri-axle limit into a hard compliance cap. For sectors handling dynamic loads such as fluid concrete and shifting aggregates, the 1TMTA functions as a compliance tolerance rather than a productivity concession. Its removal will force systematic under-loading to manage enforcement risk, eroding or negating the payload gains outlined above.

The draft Regulation also fails to provide a viable pathway for zero-emission heavy vehicles, with insufficient mass concessions and the absence of harmonised 2.55 m width settings rendering battery-electric construction vehicles commercially unviable. As shown in **Attachment 1**, battery-electric concrete agitators would incur a **payload penalty of approximately 15-16 per cent** compared to diesel equivalents due to a 2.5–3.0 tonne battery tare penalty offset by only a 0.5 tonne concession. This outcome renders zero-emission vehicles commercially unviable and conflicts with national decarbonisation objectives.

In addition, the exclusion of 20-metre “pocket” B-doubles and the continued regulatory ambiguity surrounding tri-drive rigid truck configurations represent missed opportunities to mainstream safer, more productive vehicles already operating under PBS or permit-based arrangements.

In summary, the proposed amendments represent a genuine opportunity to improve freight productivity and reduce construction costs for the Australian community. The evidence demonstrates, however, that these benefits will only be realised if the final Regulation reflects the operational realities of mass-constrained construction materials freight. CCAA therefore urges the NTC to retain the 1TMTA, explicitly link 20-metre length to Tier 1 mass limits, introduce a fit-for-purpose mass framework for zero-emission vehicles, and resolve outstanding access issues for B-doubles and tri-drive configurations.

2. Strategic Context and Regulatory Landscape

2.1 The Construction Materials Freight Task

The movement of heavy construction materials is the lifeblood of the Australian infrastructure and housing sectors. The freight task is distinguished from general logistics by the immutable physical properties of the cargo. CCA are mass-constrained commodities,

meaning the efficiency of the supply chain is strictly a function of the legal mass limits applied to axles and vehicle combinations. Unlike the retail or Fast-Moving Consumer Goods (FMCG) sectors, which often reach volumetric limits ("cube out") before reaching mass limits ("weigh out"), every kilogram of tare weight in a construction vehicle is a direct deduction from its payload and economic utility.

Specific characteristics defining this sector include:

- **High Density:** With concrete densities exceeding 2.4 tonnes per cubic metre and aggregates around 1.5 tonnes per cubic metre, vehicles operate at maximum legal mass limits on almost every laden journey.
- **One-Way Utility:** The specialized nature of the fleet - specifically concrete agitators and pneumatic cement tankers - precludes backloading. Vehicles travel laden to the delivery point and return empty, necessitating maximum efficiency on the outbound leg to justify the round-trip cost.
- **Dynamic Loading Profiles:** The sector deals with "live" loads. Concrete is a fluid that shifts its center of gravity during braking, cornering, and discharge. Aggregates settle and shift. This dynamic behavior necessitates regulatory tolerances that acknowledge the physics of the load.

2.2 The NTC Reform Agenda

The current consultation represents the culmination of the Heavy Vehicle National Law (HVNL) Review, aiming to simplify a legislative framework often criticised for being overly prescriptive and slow to adapt. By moving key mass and dimension controls from the primary Law into the *Heavy Vehicle (Mass, Dimension and Loading) National Regulation* (MDL), the NTC seeks to create a more responsive regulatory environment.¹

The core proposal to align GML with CML reflects a recognition that the modern heavy vehicle fleet is safer and more capable than the fleet for which the original GML limits were designed decades ago. Historically, accessing higher mass limits required operators to enroll in the Mass Management Module of the NHVAS, incurring significant audit and compliance costs. "Mainstreaming" these limits acknowledges that 17-tonne tandem and 21-tonne tri-axle groups are safe for general access on the established road network.

However, regulatory simplification must not come at the cost of operational reality. The interaction between the repeal of CML, the removal of the 1TMTA, and the introduction of new steer axle limits for Euro VI vehicles creates a complex matrix of winners and losers. For the CCAA, ensuring that its members are not the unintended losers of this simplification is the primary objective of this response.

3. Critical Evaluation of Proposed Regulatory Amendments

3.1 Pillar 1: Alignment of General Mass Limits (GML) with Concessional Mass Limits (CML)

The draft regulation proposes to increase the baseline GML mass limits to those currently afforded under CML. Specifically:

- **Tandem Axle Groups:** Increase from 16.5 tonnes to **17.0 tonnes**.
- **Tri-Axle Groups:** Increase from 20.0 tonnes to **21.0 tonnes**.
- **Quad Axle Groups:** Increase to **21.0 tonnes** (aligned with tri-axle limits).
- **Gross Mass Caps:** Increases are capped at +1 tonne for vehicles with a GVM \leq 55t, and +2 tonnes for vehicles $>$ 55t.¹

3.1.1 Analysis of Impact

For standard semi-trailers and B-doubles operating in the cement and general supply sectors, this is a distinct positive. It removes the administrative friction of maintaining NHVAS Mass Management accreditation for standard operations, effectively reducing the cost of compliance while securing a higher baseline payload. For a 6-axle cement tanker, this solidifies a Gross Combination Mass (GCM) of approximately 43.5 tonnes (up from 42.5 tonnes), offering a productivity dividend of roughly 2.3%.

3.1.2 The Critical Risk: Removal of the 1-Tonne Tri-Axle Mass Transfer Allowance (1TMTA)

The consultation document explicitly states that the "one tonne tri-axle mass transfer allowance" will be removed as part of this reform.¹ The 1TMTA currently allows a tri-axle group to exceed its general limit by up to 1 tonne (i.e., operating up to 21t in a GML environment) provided the total mass of the vehicle does not exceed the allowable GVM. It is a flexibility mechanism designed to account for imperfect load distribution.

The NTC's logic appears to be that since the new base limit for tri-axles is increasing to 21t (matching the CML limit), the 1TMTA - which effectively allowed 21t - is no longer needed.

This logic is flawed when applied to dynamic loads.

In the construction materials sector, the 1TMTA serves as a compliance buffer, not just a capacity booster. When a tipper loads aggregates, the loader operator cannot distribute the material with kilogram-perfect precision across the bin. Similarly, a concrete agitator's load shifts as it discharges or travels up gradients. Under the current regime (GML 20t + 1TMTA), an operator has a "soft cap" where an axle reading of 20.8t is compliant (provided steer/drive axles are lighter and GVM is under 42.5t). Under the proposed regime (New GML 21t), 21.0t becomes a hard limit. If a load shifts and the axle reads 21.2t, the operator is in breach.

Operational Implication: To avoid the risk of accidental non-compliance, operators will be forced to under-load their vehicles, effectively creating their own safety margin of 0.5t to 1.0t. This behavioural response would negate the theoretical productivity gain of the mass limit

increase. The removal of the 1TMTA transforms a flexible compliance environment into a rigid one, disproportionately penalizing sectors with shifting loads.

3.2 Pillar 2: Prescriptive Vehicle Length Increase (19m to 20m)

The draft regulation proposes increasing the general access length limit for rigid truck and trailer combinations (pig, dog, and tag trailers) from 19 metres to 20 metres.¹

3.2.1 The "Truck and Dog" Revolution

The 19-metre length limit has historically been the primary constraint for truck and dog combinations, limiting them to shorter wheelbases and drawbars which, counter-intuitively, increases bridge loading concentrations. To bypass this, the industry has heavily utilised the PBS scheme to access 20-metre lengths, which allow for "Tier 1" bridge formula compliance and a GCM of **50.5 tonnes**.

By moving the 20-metre length into the prescriptive regulation ("As-of-Right"), the NTC is effectively deregulating the PBS Level 1 truck and dog fleet. This will save operators significant costs in vehicle certification and access permits.

3.2.2 The Mass-Dimension Disconnect

A critical ambiguity in the consultation document is the relationship between this new 20m length and the associated mass limits. Length alone provides only volumetric capacity ("air space"), which is of zero value to density-constrained aggregate haulers. The productivity gain of the 20m combination lies entirely in its ability to access the **50.5-tonne** mass tier permitted under the current *National Class 3 20m Long 3-axle Truck and 4-axle Dog Trailer Mass and Dimension Exemption Notice 2024 (No. 1)*.²

If the amended Regulation increases length to 20m but retains the standard GML mass calculation (Sum of Axles capped at ~43-44t), the reform will fail to deliver its intended productivity boost. Operators would still require a Notice or Permit to access the 50.5t mass, maintaining the administrative burden. The Regulation must explicitly codify the bridge formula mass limits associated with the 20m length to ensure that 50.5t becomes the standard, permit-free limit for 7-axle combinations.

3.3 Pillar 3: Euro VI Concessions

The proposal extends the 0.5-tonne steer axle mass concession (currently for single vehicles) to road trains and twin-steer vehicles.¹

3.3.1 Twin Steer Reform

The proposal allows Euro VI twin-steer prime movers and rigid trucks to operate at **11.5 tonnes** on the steer group (up from the standard 11.0t load-sharing limit).³ This is a necessary correction. Modern Euro VI twin-steer cabs are heavier due to cooling packages

and safety structures. Without this allowance, an 8x4 concrete agitator would sacrifice payload to run a cleaner truck.

The proposal mandates load-sharing suspension and minimum 275mm tyres for this concession.¹ Most modern agitators already meet this, making it a viable transition path for the diesel fleet.

3.3.2 Road Train Inclusion

Previously, Euro VI prime movers were penalised in road train configurations (A-doubles) used extensively for remote cement delivery in WA and QLD. The 0.5t allowance for road trains removes a barrier to fleet renewal, allowing operators to deploy safer, cleaner prime movers on remote networks without a payload penalty.

3.4 Pillar 4: Tag Trailer Tow Mass Ratio

The proposal replaces the restrictive 1:1 tow mass ratio with a **1:1.3 ratio**, subject to steer axle mass requirements (Steer \geq 20% of GVM).¹

3.4.1 Analysis

The previous 1:1 ratio⁴ was a regulatory overreach that ignored engineering realities, effectively crippling the utility of tag trailers for moving plant equipment. For example, a 10-tonne rigid truck was legally restricted to towing a 10-tonne trailer, despite having the engine and braking capacity for more. The move to 1:1.3 aligns with sound mechanical principles and allows CCAA members to efficiently transport earthmoving plant (loaders, bobcats) between quarry sites using standard rigid tippers, reducing the need for separate low-loader float movements.

4. Product Category Lens Analysis

The implications of these reforms vary significantly across the CCAA's diverse membership base. The following analysis isolates the impacts for each product category.

4.1 The Concrete Lens: Agitators

Vehicle Profile: 6x4, 8x4 (Twin Steer), and 10x4 Rigid Trucks.

Current Challenge:

Concrete agitators are the most geometrically constrained vehicles in the fleet. The high center of gravity of the rotating bowl, combined with the need to navigate dense urban environments, places immense pressure on axle weight compliance, particularly on the steer axles.

Impact of Reforms:

The proposed increase of the twin-steer limit to 11.5 tonnes (for Euro VI vehicles) effectively neutralizes the weight penalty of the Euro VI emission system. However, it does not provide a net productivity gain. A standard 8x4 diesel agitator currently carries approximately 7.6m³ of concrete. The new regulations will allow a Euro VI diesel agitator to carry roughly the same amount.

Missed Opportunity:

The major missed opportunity lies in the failure to leverage the 20-metre length rule for articulated agitators. While rigid agitators dominate the market, "semi-trailer" mixers (Prime Mover + Mixer Trailer) offer significantly higher payloads (up to 10-11m³). Historically, these have been restricted by length and access issues. If the 20m length rule allows general access for semi-trailers (as implied for "Prime mover and semitrailer" combinations), this could unlock a new class of high-capacity urban agitators, reducing the total number of trucks required for large pours. We seek clarification that 20m articulated agitators will enjoy the same general access rights as 20m supply trucks.

4.2 The Aggregates Lens: Tippers and Dog Trailers

Vehicle Profile: Rigid Truck + 3, 4, or 5-Axle Dog Trailers.

Current Challenge:

The aggregate sector is currently divided into two separate directions or categories between general access vehicles (19m, ~42.5t) and PBS vehicles (20m+, 50.5t+). The administrative friction of PBS - design approvals, vehicle certifications, and network permits - adds cost and delay to fleet deployment.

Impact of Reforms:

The 20-metre prescriptive length is a game-changer. It effectively moves the "PBS Level 1" Truck & Dog into the standard fleet.

- **Operational Benefit:** Operators can purchase standard, mass-produced 20m combinations without bespoke PBS engineering fees.
- **Network Access:** By moving to "General Access," these vehicles will theoretically have access to the entire road network (subject to bridge posting), eliminating the "last mile" permit headaches often caused by local councils restricting PBS access.

Cost Analysis (Aggregates):

Assuming the regulation successfully links 20m length to the 50.5t mass limit:

- **Current Standard (19m GML):** 42.5t GCM. Tare ~14.5t. **Payload 28.0t**
- **New Standard (20m Regulated):** 50.5t GCM. Tare ~15.0t. **Payload 35.5t.**

Equals a productivity uplift of +7.5 tonnes per trip (+27%).

- **Cost to Serve:** With a base cost of \$0.15/t/km for the baseline vehicle, the trip cost for 100km is \$420 (28t * \$15).
 - New Cost per Tonne: $\$420 / 35.5t / 100km = \mathbf{\$0.118 \text{ per t/km}}$.
 - **Savings: 21.3% reduction in transport costs.**

4.2.1 Resolving the Tri-Drive Ambiguity

Resolving the Tri-Drive Ambiguity A critical barrier to the adoption of safer, high-traction vehicles in the quarrying sector has been the regulatory confusion regarding tri-drive (tridem drive) rigid trucks. While the National Class 2 PBS Level 1 & 2A Truck and Dog Trailer Authorisation Notice 2024 (No.2) legally defines an eligible vehicle as a "3 or 4 axle rigid truck" —a definition that technically includes 4-axle tri-drive units—the associated NHVR Information Sheet explicitly excludes them.

This contradiction forces operators who invest in high-traction tri-drive vehicles (essential for safety in steep quarry environments) to bypass the efficient Notice system and apply for individual PBS permits, adding unnecessary cost and delay.

Implication for Reform: With the proposal to increase GML limits for tri-axle groups to 21.0 tonnes and move 20m combinations into prescriptive regulation, the NTC has the opportunity to resolve this. The new prescriptive definition for a 20m Rigid Truck and Dog must explicitly enable tri-axle drive groups on the rigid truck, aligning them with the new GML mass limits and acknowledging their bridge-loading friendliness (distributing mass over more axles).

4.3 The Cement Lens: Pneumatic Tankers

Vehicle Profile: 19m B-Doubles ("Pocket B-Doubles"), 26m B-Doubles, A-Double Road Trains.

Current Challenge:

Cement is a high-density powder. Tankers always "weigh out" before they "cube out." Maximizing mass within fixed dimension envelopes is the sole driver of efficiency.

Impact of Reforms:

- **Road Trains:** The 0.5t steer axle concession is critical for A-double road trains servicing remote batch plants. It allows the use of modern, heavier prime movers without sacrificing 500kg of cement payload.

- **B-Doubles:** The alignment of GML to CML provides a payload boost for B-doubles. A 9-axle B-double currently at 62.5t (GML) moves to a potential ~64.5t (capped increase).
- **Payload Gain:** ~2.0 tonnes.
- **Cost Analysis (Cement):**
 - Base Cost: \$0.30/t/km. Trip Cost (200km, 40t load) = \$2,400.
 - New Payload: 42t.
 - New Cost: \$2,400 / 42t / 200km = **\$0.285 per t/km.**
 - **Savings: 5.0% reduction in transport costs.**

It is noted that major cement producers already operating under NHVAS Mass Management and CML settings will not realise a material payload or cost benefit from this change. For these operators, the principal benefit is regulatory simplification and the potential reduction in audit and administrative costs associated with maintaining mass accreditation, while continuing participation in NHVAS Maintenance and Fatigue modules

Missed Opportunity:

The consultation document notes that increasing the length of "short" B-doubles from 19m to 20m is not in this package but is "Further amendments... to be developed".¹ This is a disappointment for the cement sector, where "Pocket B-Doubles" are heavily used for urban distribution. Increasing their length to 20m would allow for better axle spacing (bridge formula compliance) and potentially higher mass limits like the truck and dog reform.

5. Critical Gap Analysis: The Decarbonisation Disconnect

The most significant failure of the proposed regulation is its inability to support the transition to low-emission vehicles – with the current draft regulations actively discouraging it.

5.1 The "Green Weight Penalty"

Battery Electric Vehicles (BEVs) are significantly heavier than diesel trucks due to the low energy density of lithium-ion batteries compared to diesel fuel, per:

- **Diesel 8x4 Agitator Tare: ~11.5 tonnes.**
- **Electric 8x4 Agitator Tare: ~14.2 - 14.5 tonnes.⁵**
Equals a weight penalty of ~2.7 - 3.0 tonnes.

and

- **Diesel 6x4 Prime Mover Tare: ~8.2 tonnes**
- **Battery-Electric 6x4 Prime Mover Tare: ~12.2 tonnes**
Equals a weight penalty of ~4.0 tonnes.

5.2 Why the Proposal Fails

The proposed concession for Euro VI/Low Emission vehicles is **0.5 tonnes** on the steer axle (6.5t -> 7.0t) or twin steer group (11.0t -> 11.5t) ¹ is inadequate because:

- **The Math:** An electric agitator gains +0.5t in legal allowance but loses ~3.0t in payload capacity due to battery weight.
- **Net Payload Loss: -2.5 tonnes.**
- **Concrete Equivalence:** 2.5 tonnes is approximately **1.0 m³** of concrete.
- **Commercial Impact:** A standard diesel agitator delivers ~7.6 m³. An electric agitator under the proposed rules would be legally restricted to ~6.6 m³. This represents a **13% loss in revenue per trip.**

In an industry with thin margins, a 13% productivity penalty is an insurmountable barrier to adoption. Operators cannot charge 13% more for "green concrete" to cover the transport inefficiency, nor can they simply run 13% more trips (which would increase congestion and non-tailpipe emissions like brake dust).

5.3 Benchmarking International Best Practice

Other jurisdictions have recognised this gap. The European Union's Weights and Dimensions Directive grants a **2.0-tonne** additional mass allowance for zero-emission heavy duty vehicles to ensure payload parity with diesel.⁶ Within Australia, the New South Wales and Queensland governments have initiated trials allowing **8.0 tonnes** on single steer axles and up to **18.5 tonnes** on drive axles for electric trucks.⁷

The NTC's proposal ignores these precedents, adhering to a conservative 0.5t increase derived from the weight of a Euro VI exhaust muffler, rather than the weight of a battery pack.

5.4 Recommendations for ZLEV Support

To align with National Net Zero targets, the MDL Regulation must include a specific schedule for Zero Emission Heavy Vehicles (ZEHVs) that provides:

1. **Steer Axle Mass: 8.0 tonnes** for single steer axles and **13.0 tonnes** for twin steer groups.
2. **Gross Vehicle Mass:** A **2.0-tonne** concession on GVM caps (e.g., allowing a 3-axle rigid EV to run at 24.5t instead of 22.5t).
3. **Width:** Full harmonization with the 2.55m width standard (without restrictive safety package conditions that might not yet be available on all EV models) to allow the importation of global EV truck platforms.

6. Economic and Community Benefit Quantification

The proposed reforms, if implemented with the recommended adjustments (specifically linking 20m length to 50.5t mass), will deliver substantial benefits to the wider Australian community.

6.1 Reduced Truck Journeys

By increasing the payload of the standard aggregate truck from 28t to 36t, the industry can move the same volume of material with significantly fewer trips.

- **Scenario:** Transporting 1 million tonnes of quarry products.
- **Current State (19m):** 35,714 truck trips.
- **Future State (20m):** 27,778 truck trips.
- **Result: 7,936 fewer truck trips** on public roads (-22%). This directly correlates to reduced congestion, lower road wear, and a reduction in crash exposure risk for light vehicle road users.

6.2 Reduced Greenhouse Gas Emissions

While individual heavier trucks burn marginally more fuel, the reduction in total trip numbers drives a net reduction in fleet emissions.

- **Assumptions:** Diesel consumption 55L/100km (Current) vs 60L/100km (Heavier Future).
- **Current Usage:** $35,714 \text{ trips} * 100\text{km} * 0.55 = 1,964,270 \text{ Litres}$.
- **Future Usage:** $27,778 \text{ trips} * 100\text{km} * 0.60 = 1,666,680 \text{ Litres}$.
- **Net Savings: 297,590 Litres of diesel.**
- **CO2 Avoided:** Approximately **800 tonnes of CO2** per million tonnes of freight moved.

6.3 Lower Construction Costs

Reducing the transport cost component of raw materials lowers the input costs for housing and infrastructure.

Aggregate Savings: Cost to serve drops from \$0.150 to \$0.117 per t/km. On a major highway project requiring 500,000 tonnes of base course hauled 50km, this represents a saving of **\$825,000** to the taxpayer.

References

1. Heavy Vehicle (Mass, Dimension and Loading) National Regulation Amendment consultation overview_0.pdf
2. National Class 3 20m Long 3-axle Truck and 4-axle Dog Trailer Mass and Dimension Exemption Notice Operator's Guide | NHVR, accessed December 18, 2025, <https://www.nhvr.gov.au/C2024G00257-national-class-3-20m-long-3-axle-truck-and-4-axle-dog-trailer-mass-and-dimension-exemption-notice-2024-no1-operators-guide>
3. ADR 80/04 (Euro VI) emissions mass limits increase - Information sheet - | NHVR, accessed December 18, 2025, <https://www.nhvr.gov.au/files/media/document/561/202411-1575-adr-80-04-euro-iv-emissions-mass-limits-increase-v1.1.pdf>
4. HVIA Puts Tag Trailer Mass Back On The Reform Agenda - Heavy Vehicle Industry Australia, accessed December 18, 2025, <https://hvia.asn.au/hvia-puts-tag-trailer-mass-back-on-the-reform-agenda/>
5. FOTON e AUMAN C Mixer Bus The EV Concrete Truck Mixer for today! Low Power Consumption. CATL Battery., accessed December 18, 2025, <https://43078166.fs1.hubspotusercontent-na1.net/hubfs/43078166/A4%20FOTON%20EV%20Concrete%20Truck04.pdf>
6. Position Paper - Revision of the Weights and Dimensions Directive - ACEA, accessed December 18, 2025, <https://www.acea.auto/files/ACEA-position-paper-Revision-of-the-Weights-and-Dimensions-Directive.pdf>
7. Qld Government rolls out axle weight increase for electric trucks - trucksales.com.au, accessed December 18, 2025, <https://www.trucksales.com.au/editorial/details/qld-government-rolls-out-axle-weight-increase-for-electric-trucks-144954/>
8. NSW zero emission heavy vehicle access trial, accessed December 18, 2025, <https://www.transport.nsw.gov.au/operations/freight-hub/towards-net-zero-emissions-freight-policy/nsw-zero-emission-heavy-vehicle>

Attachment 1: Comparative Analysis of Productivity Gains by Sector

Sector	Configuration	Current Limit (GML)	Proposed Limit	Net Payload Impact	Cost to Serve Impact****
Aggregates	19m Truck & Dog	42.5t (28t Payload)	50.5t (36t Payload)*	+28.5%	-21.3%
Cement	26m B-Double	62.5t (40.5t Payload)	64.5t (42.5t Payload)	+4.9%	-5.0%***
Cement	6x4 Electric Prime Mover	N/A	62.5t (36.5t Payload)***	-9.9% (vs Diesel)	+11.0%
Concrete	8x4 Diesel Agitator	27.5t (16t Payload)	28.5t (17t Payload)	+6.2%	-5.8%
Concrete	8x4 Electric Agitator	N/A	28.5t (13.5t Payload)**	-15.6% (vs Diesel)	+18.5%

*Assuming 20m length is linked to 50.5t mass.

**Assuming 3.0t battery penalty and only 0.5t steer concession.

*** Assumes operators not currently operating under NHVAS Mass accreditation. Large accredited cement fleets will experience limited direct cost or payload change.

**** **Cost to serve** refers to the average transport cost per tonne of material delivered, taking into account vehicle operating costs and payload carried.

Attachment 2: Australian Road Freight Transport – National and Jurisdictional Metrics (All Commodities vs Construction-Materials Sector)

AUSTRALIAN ROAD FREIGHT TRANSPORT (ALL VS CCA INDUSTRY)									
	QLD	NSW	VIC	TAS	SA	NT	WA	TOTALS	
Total road freight transport (all commodities)	Annual trailers	5,055,681	6,042,728	4,645,434.48	709,414.53	1,425,384.64	203,814.61	4,770,479.32	22,852,936
	Annual tonnes	98,580,869	121,600,672	92,278,274	13,997,706	30,652,553	3,986,519	104,953,792	466,050,385
	Tonne kilometres (billion t kms)	25.55	24.75	14.51	2.71	6.54	1.50	30.75	106.3
	Tonnes/trailer (average)	16.3	16.9	16.5	16.7	16.9	14.8	16.9	16.4
	Avg Trip Distance (km) (average)	144.4	104.8	83.8	99.5	101.0	154.8	147.9	119.5
	Avg Trip Duration (hrs) (average)	1.6	1.2	1.0	1.1	1.2	2.2	1.6	1.4
	Cost per payload tonne (\$) (average)	\$ 54.54	\$ 36.76	\$ 26.30	\$ 39.82	\$ 30.66	\$ 82.49	\$ 41.32	\$ 44.55
	Cost per tonne km (\$) (average)	\$ 0.38	\$ 0.35	\$ 0.38	\$ 0.38	\$ 0.39	\$ 0.43	\$ 0.39	\$ 0.38
Total transport costs (\$)	\$ 2,698,907,482	\$ 2,525,813,332	\$ 1,456,155,721	\$ 297,111,881	\$ 593,587,827	\$ 105,670,530	\$ 3,300,406,952	\$ 10,977,653,725	
CCA sector only (clinker, cement, rock, sand, gravel & concrete commodities only)	Annual trailers	2,022,394	3,286,747	2,080,274.13	175,877	463,663.01	125,347.71	734,768.68	8,889,072
	Annual tonnes	41,517,152	67,572,576	42,535,712	3,835,877	9,738,726	2,568,172	15,140,055	182,908,270
	Tonne kilometres (billion t kms)	7.79	5.18	2.20	0.61	1.91	0.97	3.47	22.1
	Tonnes/trailer (average)	20.5	20.4	20.3	21.6	20.4	21.1	20.4	20.7
	Avg Trip Distance (km) (average)	91.7	76.6	49.4	79.5	97.9	185.1	110.2	98.6
	Avg Trip Duration (hrs) (average)	1.1	0.9	0.6	1.0	1.2	2.6	1.2	1.2
	Cost per payload tonne (\$) (average)	\$ 16.62	\$ 13.49	\$ 8.64	\$ 9.86	\$ 12.57	\$ 19.69	\$ 15.12	\$ 13.71
	Cost per tonne km (\$) (average)	\$ 0.23	\$ 0.24	\$ 0.27	\$ 0.25	\$ 0.22	\$ 0.17	\$ 0.20	\$ 0.23
Total transport costs (\$)	\$ 689,963,087	\$ 911,558,853	\$ 367,546,025	\$ 37,806,364	\$ 122,379,407	\$ 50,575,278	\$ 228,984,359	\$ 2,408,813,373	
CCA/Total	Annual trailers	40%	54%	45%	25%	33%	62%	15%	39%
	Annual tonnes	42%	56%	46%	27%	32%	64%	14%	39%
	Tonne kilometres (billion t kms)	30%	21%	15%	23%	29%	65%	11%	21%
	Total transport costs (\$)	26%	36%	25%	13%	21%	48%	7%	22%
CCA +/- % (compared to total averages)	Tonnes/trailer (average)	26%	20%	23%	29%	21%	42%	21%	26%
	Avg Trip Distance (km) (average)	-36%	-27%	-41%	-20%	-3%	20%	-25%	-19%
	Avg Trip Duration (hrs) (average)	-35%	-23%	-35%	-15%	2%	15%	-23%	-16%
	Cost per payload tonne (\$) (average)	-70%	-63%	-67%	-75%	-59%	-76%	-63%	-68%
Cost per tonne km (\$) (average)	-39%	-31%	-28%	-34%	-44%	-60%	-48%	-41%	

Source: CSIRO Transport Network Strategic Investment Tool (2025 data)